

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 02/01/07	~	LJC 02/01/07
B	整理圖面	YCH 08/15/07	~	



NOTES:



- ELECTRICAL CHARACTERISTICS:
 - CONTACT RESISTANCE: 30mΩ Max.INITIAL.
 - DIELECTRIC WITHSTANDING
VOLTAGE:500V AC(rms) FOR 1 MINUTE.
 - INSULATION RESISTANCE:1000MΩ Min.
- MECHANICAL CHARACTERISTICS:
 - DURABILITY: 300 CYCLES.
- ENVIRONMENT CHARACTERISTICS:
 - TEMPERATURE RANGE: -40°C~+105°C.
- PRODUCT NUMBER CODE:
DS1036 - XX X X X X X X

SCREW TYPE
X:W/O SCREW
1:CC TYPE
2:CS TYPE
RIVET TYPE
P:W/ THREAD(UNC #4-40)
N:W/O THREAD
CONTACT PLATING
Si: SELECTIVE GOLD FLASH
HOUSING COLOR
U:BLUE
B:BLACK
STRAIN RELIEF
P:W/
N:W/O
CONNECTOR TYPE
M:MALE
F:FEMALE
No.OF CONTACTS
09:9pos 15:15pos
25:25pos 37:37pos

Position	A±0.1	B±0.2	C±0.2	D±0.2		E±0.2
				Male	Female	
9P	10.16	30.80	24.99	17.90	16.33	19.00
15P	17.78	39.14	33.32	26.50	24.66	27.34
25P	30.48	53.04	47.04	40.00	38.38	41.24
37P	45.72	69.32	63.50	56.50	54.84	57.52


UPPER COVER



GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	
X.	±0.60	X.	±3°	UNITS	mm	I.D.C D-SUB	
.X	±0.38	.X	±2°	SHEET SIZE	A4	SERIES	DS1036 SERIES
.XX	±0.25	.XX	±1°	<div> 晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD</div>			
DRAWING TYPE		CUSTOMER					
SCALE	1:1	SHEET	1 OF 1				
DRAWING NO.	C-DS1036-XXXXXXX						




晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD




Male


W/O SCREW TYPE



CC TYPE



CS TYPE



Female